

# SLEDGE



All in one RFID Scanner



Sledge (C72) is an industrial-grade Android mobile computer. The device ensures powerful barcode scanning performance that can accurately & quickly read various Symbologies of 1D/2D barcode labels even if the barcode is dirty, damaged, or wrinkled. In addition, Sledge (C72) features Android 11 OS, Octa-core processor, 8000mAh powerful battery, 13 MP camera, and optional NFC reading.

# SPECIFICATIONS



## PHYSICAL CHARACTERISTICS

<b>Dimensions</b>	164.2 x 80.0 x 24.3 mm / 6.46 x 3.15 x 0.96 in.
<b>Weight</b>	654 g / 23.07 oz.
<b>Display</b>	5.2" IPS LTPS 1920 x 1080
<b>Touch Panel</b>	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
<b>Power Supply</b>	Main battery: Li-ion, rechargeable, 8000 mAh Standby: over 500 hours Continuous use: over 12 hours (depending on user environment) Charging time: 3-4 hours (with standard adaptor and USB cable)
<b>Notification</b>	Sound, LED indicator
<b>Expansion Slot</b>	1 slot for Nano SIM card, 1 slot for Nano SIM or TF card
<b>Interfaces</b>	USB 2.0 Type-C, OTG, Type-C headphones supported
<b>Audio</b>	1 microphone ; 1 speaker ; receiver
<b>Keypad</b>	4 front keys, 1 power key, 2 scan keys, 1 multifunctional key
<b>Sensors</b>	Light sensor, proximity sensor, gravity sensor

## DEVELOPING ENVIRONMENT

<b>Operating System</b>	Android 11; GMS, FOTA, Soti MobiControl, SafeUEM supported. Committed support for a future upgrade to Android 12, 13, and Android 14 pending feasibility
<b>SDK</b>	Software Development Kit
<b>Language</b>	Java
<b>Tool</b>	Eclipse / Android Studio

## USER ENVIRONMENT

<b>Operating Temp.</b>	4 °F to 122 °F / -20 °C to 50 °C
<b>Storage Temp.</b>	-40 °F to 158 °F / -40 °C to 70 °C
<b>Humidity</b>	5% RH - 95% RH non condensing
<b>Drop Specification</b>	Multiple 1.5 m / 4.9 ft. drops (at least 20 times) to the concrete across the operating temperature range
<b>Tumble Specification</b>	1000 x 0.5 m / 1.64 ft. falls at room temperature
<b>Sealing</b>	Host IP65 per IEC sealing specifications
<b>ESD</b>	±15 KV air discharge, ±6 KV conductive discharge



## CAMERA

<b>Camera</b>	13 MP Autofocus with flash
---------------	----------------------------

## COMMUNICATION

<b>WLAN</b>	IEEE802.11 a/b/g/n/ac, 2.4G/5G dual-band, internal antenna
<b>WWAN</b>	2G: GSM850/GSM900/DCS1800/PCS1900 3G: WCDMA : B1/B2/B4/B5/B8 CDMA2000 EVDO: BC0 TD-SCDMA : A/F 4G:B1/B2/B3/B4/B5/B7/B8/B12/B17/B20/B28A B28B/B34/B38/B39/B40/B41
<b>WWAN (Others)</b>	Depending on the country's ISP
<b>Bluetooth</b>	Bluetooth 5.0
<b>GNSS</b>	GPS/AGPS, GLONASS, BeiDou; internal antenna
<b>Note</b>	*Sledge (C72) models being manufactured for Turkish Market, do not include Voice Call (Phone Call) function. WAN module included on those models only support DATA transfer.

## PERFORMANCE

<b>CPU</b>	Cortex-A53 2.3 GHz Octa-core
<b>RAM+ROM</b>	3GB + 32GB 4GB + 64GB (optional)
<b>Expansion</b>	Supports up to 128 GB Micro SD card



## BARCODE SCANNING

<b>1D Linear Scanner</b>	Zebra: SE965; Honeywell: N4313
<b>2D Imager Scanner</b>	Zebra: SE4710 / SE4750SR / SE4750MR / SE4750DP; Honeywell: N6603
<b>1D Symbologies</b>	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
<b>2D Symbologies</b>	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc.
<b>Note</b>	*This function is optional

## NFC

<b>CPU</b>	13.56 MHz
<b>RAM+ROM</b>	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
<b>Expansion</b>	M1 card (S50, S70), CPU card, NFC tags, etc.
<b>Range</b>	2-4 cm